

Bergshav Management AS

MACHINERY

Propeller:	IHI, 5 Bladed Keyless Ni-Al-Bronze, Pitch 5095 mm, Diameter 6800 mm, Weight 23.7 MT
Main Engine:	1 x 6-Cyl, 2-Stroke, Single Acting, Turbo charged, MITSUI MAN-B&W Diesel Engine, Type 6S60ME-C, MCR 13 560 kW @ 105 rpm
Bow Thruster:	Brunvoll 4 Bladed CP, 2000 kW x 900 rpm (Electric), Ni-Al-Bronze, Diameter 2450 mm, Nominal Thrust 260 kN
Anchor:	2 x 9225 kg HHP
Chain:	Flash Butt welded, Grade K3, Diameter 87 mm, Total length - 687.5 m (12 Sh each), trs, Total weight; 116.25 T.

CARGO CAPACITIES

Cargo tanks:	1 to 6 P&S COT & 2 SLOP TANKS.
Cargo Manifold:	3 x 400 mm (16")
Cargo Capacity (98%):	COT 114 413.3 m ³ + SLOPS 4 650.7 m ³ = 119 064 m ³
Max. Loading rate:	15 000 m ³ /h
Mast Riser venting cap:	15 000 m ³ /h